

Window, Door  
and  
Curtain Wall Testing

**AAMA/WDMA/CSA 101/I.S.2/A440-08**

**TEST REPORT**

**Render to:**  
**CT International Aluminum Corp.**

TITLE	SUMMARY OF RESULTS
Product manufacturer:	CT International Aluminum Corp
Product type:	Sliding Door
Product series/ model:	CT-43 Series
Primary product designator:	Class: CW - PG30 SD 94"x95" ( 2387.6 mm x 2413mm)
Force entry resistance:	Grade 10
Air infiltration @6.24 PSF :	0.19 cfm/ft <sup>2</sup> ( 0.95 L/sm <sup>2</sup> )
Water penetration resistance:	4.5 Psf (215 Pa)
Test completion date:	03/24/15
<b>Report # 14-032-A</b>	





## Window, Door and Curtain Wall Testing

**Report No:** 14-0032-A  
**Test Completion Date:** 3-24-15  
**Report Date:** 4-20-15  
**Report Retention Date:** 4-20-25

**Client:**  
CT International Corp  
5235 74<sup>th</sup> Street  
Elmhurst, NY 11373

### Test Specification

**AAMA/WDMA/CSA 101/LS2/A440-08 "NAFS North American Fenestration  
Standard/Specification for Windows, doors, and unit skylights".**

### Test Specimen Designation

**Model: CT 43 Series Patio Door**

**Class: CW - PG30 SD 2387.6 mm x 2413 mm (94"x95")**

**MT** Group

145 Sherwood Av  
Farmingdale, NY 11735  
(631) 815-1920 Office  
(631) 815-1901 Fax

**MT** Group

**MT** Group

403 County Rd, Suite 1  
Cliffwood, NJ 07721  
(732) 725-6177 Office  
(732) 725-6180 Fax

**MT** Group

**MT** Group

**MT** Group

Page 2 of 8  
Report # 14-0032-A



# Window, Door and Curtain Wall Testing

## Frame

The frame members are extruded aluminum.

Overall dimensions are 94"x95" ( 2387.6 mm x 2413mm)

**Head:** part no 4304

**Sill:** part no 4321

**Jambs:** part no 4305.

**Bottom Corners:** Are butt and coped and held together with five screws (1.5" long no. 12-14 with a 5/16 flange-ed hex head drive) per corner.

**Top Corners:** Are butt and coped and held together with Three screws (1.5" long no. 12-14 with a 5/16 flange-ed hex head drive) per corner.

## Sash

Sash members are made of extruded aluminum. The Overall dimensions of both sashes is 1041.4 mm x 2159 mm (41" x 85").

**Top/Bottom Rail :** Part no. 4301

**Left/Right Styles:** Part no. 4300.

**Corners:** Coped and Butted together with two 3.5" 12-14 screws per corner with no. 3 Philips drive button head.

**Inter locker:** part no 4302. Located on meeting styles. Fastened to meeting styles with no2 Philips button head drive no. 12-20 3/8" long screws

MT Group	MT Group	MT Group	MT Group	MT Group	MT Group
145 Sherwood Av Farmingdale, NY 11735 (631) 815-1920 Office (631) 815-1901 Fax		403 County Rd, Suite 1 Cliffwood, NJ 07721 (732) 725-6177 Office (732) 725-6180 Fax			Page 3 of 8 Report # 14-0032-A



# Window, Door and Curtain Wall Testing

## Weather seals:

QTY	Location	Description
1 row	Sill leg	Polly mid fin wool pile 0.270" backing 0.25" tall
1 row	Sill threshold cover	Polly mid fin wool pile 0.270" backing 0.25" tall
1 row	Head	Bulb gasket for non operable unit
1 row	Head outer leg	Polly mid fin wool pile 0.270" backing 0.25" tall for operable unit
1 row	Head	Polly mid fin wool pile 0.270" backing 0.4" tall for operable unit supported with additional extrusion fastened to head with screws
2 rows	Top rail operable door	Polly mid fin wool pile 0.270" backing 0.25" tall on each door flange
2 rows	One for each interlock	Polly mid fin wool pile 0.270" backing 0.25" tall
3 rows	Operable jamb	Bulb gasket, two for operable door and one is for jamb insert
4 pcs	Frame Butt connections	foam rubber sheet gasket placed in-between butt joins
2 rows	fixed jamb	Bulb gasket, one for fixed panel door and one is for jamb insert

## Glazing:

Glass Size	IG thickness	Glass thickness	Glass type	Spacer Thickness	Spacer type	Identification
35 1/8" x 78" (892.2mm x 1981.2mm)	1" (25.4 mm)	3/16"	tempered	5/8" (15.9 mm)	Aluminum	Local vendor

The unit is channel glazed using a rubber channel glazing gasket. There is a 12.7 mm (1/2") glass bite. There is two panes of glass same thickness.

## Drainage System:

QTY	Title	Description	location
2	Weeps	0.275" tall x 1-5/8" wide includes anti clog baffle and flapped weep hole cover	Either end of sill on front face centered 2.5" from edge of unit



# Window, Door and Curtain Wall Testing

## Hardware:

QTY	Title	Location	Description
1	Keeper	Centered at 41.5" from bottom of unit on operable frame jamb	Metal Keeper held in with two screws
1	Handle set	In operable door style Centered at 40.5" from bottom of sash	bottom sash rail 9" from edge

## Reinforcements:

Two solid aluminum reinforcements in each meeting style. Each measuring about 1.25" deep and 0.6" wide for a total of four of these.

## Interior & Exterior Surface Finish:

Natural Aluminum mill Finish

## Sealant Application:

Sealant is applied to frame and sash corners, In the glazing track, stationary door perimeter, the threshold, jamb insert, and is used to plug door rails.

## Insect Screen:

None



# Window, Door and Curtain Wall Testing

## Installation:

Unit is installed into a 2x8 Douglas fir buck with a blind stop on both sides of the door fastened to the buck with 1-5/8" dry wall screws every foot.

## Operating Force Test Results

Paragraph No.	Test title & (Method)	Results	Allowed	Allowed
5.3.1.2	Operating Force	ASTM E2068	180N (40 lbf) in motion	115N (25 lbf) in motion

Sizes	Operable Door	
Sash open break away	20 Lbf (90N)	
Sash close break away	20 Lbf (90N)	
Sash open in-motion	18 Lbf (80N)	
Sash close in-motion	18 Lbf (80N)	

## Resistance against opportunistic Burglar

Paragraph	Test	Result	Allowable	
(5.3.5)	Forced Entry ASTM F588	No Entry Grade 10	No Entry	

## Air and Water Test Results

MT Group	MT Group	MT Group	MT Group	MT Group	MT Group
145 Sherwood Av Farmingdale, NY 11735 (631) 815-1920 Office (631) 815-1901 Fax		403 County Rd, Suite 1 Cliffwood, NJ 07721 (732) 725-6177 Office (732) 725-6180 Fax		Page 6 of 8 Report # 14-0032-A	



# Window, Door and Curtain Wall Testing

Paragraph	Test	Result	Allowable
(5.3.2)	Air Infiltration ASTM E283 @300 Pa (6.24psf)	Pass 0.95 L/sm2 0.19 cfm/ft2	1.5 L/sm2 0.3 cfm/ft2
(5.3.2)	Air Infiltration ASTM E283 @75 Pa (1.57psf)	Pass 0.6 L/sm2 0.12 cfm/ft2	1.5 L/sm2 0.3 cfm/ft2
(5.3.3)	Cyclic Water Penetration ASTM E547 @ 220 Pa (4.5Psf)	Pass	No Water

## Structural Testing Results

Paragraph	Test	Result	Allowable
(5.3.4.2)	Preload ASTM E330 @ 718 Pa Positive (15 PSF)	Pass	No breakage
(5.3.4.2)	Uniform Load max Deflection ASTM E330 @ 1436 Pa Positive (30 PSF)	Pass 0.48" (12 mm)	L/175 0.53" (13.5 mm)
(5.3.4.2)	Uniform Over load permanent Deflection ASTM E330 @ 2155 Pa (Positive 45 PSF)	Pass 0.02" (0.51 mm)	0.3% L 0.28" (7.11 mm)
(5.3.4.2)	Preload ASTM E330 - 718 Pa Negative (-15 PSF)	Pass	No breakage
(5.3.4.2)	Uniform Load Max Deflection ASTM E330 - 1436 Pa Negative (-30 PSF)	Pass 0.52" (13.21mm)	L/175 0.53" (13.5 mm)
(5.3.4.2)	Uniform Over load permanent Deflection ASTM E330 @ - 2155 Pa ( Negative 45 PSF)	Pass 0.04" (1.02mm)	0.3% L 0.28" (7.11 mm)

## Deglazing Test (ASTM E 987) Results

MT Group	MT Group	MT Group	MT Group	MT Group
145 Sherwood Av Farmingdale, NY 11735 (631) 815-1920 Office (631) 815-1901 Fax		403 County Rd, Suite 1 Cliffwood, NJ 07721 (732) 725-6177 Office (732) 725-6180 Fax		Page 7 of 8 Report # 14-0032-A




# Window, Door and Curtain Wall Testing


Paragraph 5.3.6.3	Test Feature	Results	Allowed
320 N (70Lbf) Interior	Left Style	12.00%	<90%
	Right Style		
230 N (50Lbf) Interior	Top Rail	12.00%	<90%
	Bottom Rail		
320 N (70Lbf) Middle	Left Style	12.00%	<90%
	Right Style		
230 N (50Lbf) Middle	Top Rail	12.00%	<90%
	Bottom Rail		
320 N (70Lbf) Exterior	Left Style	12.00%	<90%
	Right Style		
230 N (50Lbf) Exterior	Top Rail	12.00%	<90%
	Bottom Rail		

This report is prepared for the convenience of our customers and endeavors to provide accurate and timely project information. It is the exclusive property of the client so named herein and relates only to the specimen(s) tested. It contains a summary of observation made by a qualified representative of Materials Testing Lab, Inc. This report is intended to help in your Quality Assurance Program, but it does not represent a continuous nor exhaustive evaluation. The statements made herein do not constitute approval, disapproval, certification, or acceptance of performance or materials. This report may not be reproduced, except in full, without the written approval of Materials Testing Laboratories, Inc.

*A copy of this report will be retained by Materials Testing Lab, Inc, for a period of seven years.  
This report is the exclusive property of the client so named herein.*

For Materials Testing Lab, Inc.

  
Craig Ginsberg  
Mechanical engineer  
4/16/15

Approved by:   
Frank Pennisi  
Vice President  
4/16/15