
	8000 series	7000 series	5000 series
Specifications			
Pivot Point	6 5/8", 8 5/8", 10"	6 5/8" and 8 5/8"	6 5/8", Small Field
Towable Pivot Point	2-Wheel E-Z Tow, 4-Wheel E-Z Tow, Skid Tow	Not Available	3 Point Hitch, 2-Wheel E-Z Tow, 4-Wheel E-Z Tow
Maximum Towing Length	2800'	Not Available	660'
Pipe Diameters	6", 6 5/8", 8 5/8", 10"	6", 6 5/8"	5"
Span Lengths	115', 135', 140', 160', 180', 185', 187', 205', 225'	115', 135', 140', 160', 180', 185', 187', 205'	112.5', 135', 157.5', 180', 202.5'
Overhang Lengths	9', 18', 27', 36', 45', 54', 64', 73', 82', 100'	Same as 8000 series	19.2', 28.5', 37.7', 55.9'
<b>Booster Pump Option</b>	2 HP, 5 HP, and 7.5 HP	2 HP and 5 HP	1 HP for single phase, 2 HP
Available Tire Sizes	11.2 x 24", 11.2 x 38", 11x 22.5", 14.9 x 24", 16.9 X 24", 18.4 x 26",	Same as 8000 series	11.2 x 24", 11x 22.5", 14.9 x 24"
157.5' Span Weight (lbs) - Wet	6200 (6 5/8")	5900 (6 5/8")	4400 (5")
180' Span Weight (lbs) - Wet	6800 (6 5/8")	6400 (6 5/8")	4900 (5")
205' Span Weight (lbs) - Wet	7500	7100	5400 (5" - 202.5')
Truss Rods	3/4", 13/16", 7/8"	11/16", 3/4" (on 205' only)	5/8"
Truss Angle	2 X 2 X 3/16"	2 X 2 X 1/8"	2 X 2 X 1/8"
Drive Leg	3 X 3 X 1/4"	3 X 3 X 3/16"	3 X 3 X 3/16"
Span Connection	Ball & Socket	Ball & Socket	Internal Connection
Corner Arm Available	•	•	
480v Engine Generator	•	•	•
Floatation Options	3-Wheel Drive, Articulating 4-Wheel Drive, Track Drive, Articulating Track Drive, agri-TRAC, RAAFT Track	3-Wheel Drive	
Profile	Low, Standard, High, & Ultra High	Low & Standard	Low & Standard
Maximum Machine Length	2800'	1500'	820'
Drive Train	Valley & Valley HD	VS-7000 & Valley	VS-7000
Single Phase			•
Bender30/160	•	•	
DropSpan	•	•	



See your local authorized Valley dealer for complete details.











©2014 Valmont Industries, Inc., Valley, NE 68064 USA. All rights reserved.

WWW.valleyirrigation.com

AD11180 C 09/14