

# Valley Rainger™ Linear





The Valley Rainger™ provides water source versatility with ditch (canal) and hose (pressured pipeline) feed, and also has customized cart options. Valley Rainger linears offer high-flow capabilities that are not available with other mechanized irrigation equipment.

The Valley Rainger gives you the ability to customize the equipment to fit your field. Begin with the Valley linear basic cart, equipped with the durable 5 inch tube frame. The same frame is used no matter your water source – you select what you need.

### Ditch Feed

Water Source	Earthen ditch or concrete canal
Power Source	Cart-mounted engine
Guidance	GPS, above- or below-ground cable, or furrow
Typical Field Sizes	130-607 hectares (301-1500 acres)
Typical Flow Rates	32-285 lps (500-4500 gpm)
Chemigation	On-board tanks



### Hose Feed

Water Source	Pressurized pipeline
Power Source	Cart-mounted engine or power cord
Guidance	Above- or below-ground cable, or furrow
Typical Field Sizes	9-47 hectares (22-67 acres)
Typical Flow Rates	12-88 lps (200-1400 gpm)
Chemigation	On-board tanks



### Swing Around

The Rainger Swing-Around can be configured to cover a wide range of field widths. It rotates 180° around the cart to irrigate the opposite side of the field. This linear provides an economical solution, doubling the amount of land irrigated with one machine.

- Utilizes the ClassicPlus or AutoPilot Linear control panel
- Available as a hose drag or ditch feed
- Above-ground, below-ground, or furrow guidance