



501 - ACRYLIC ROOF COATING
ELASTOMERIC – WHITE



AND

501 - ACRYLIC BASE COAT
ELASTOMERIC - LIGHT GRAY



501 - ACRYLIC IS READY FOR USE WITH NO STIRRING NECESSARY. 501 is 100% ACRYLIC, and it will seal and protect a variety of surfaces.

501 - ACRYLIC ROOF COATING provides considerable cooling, and therefore, lengthens the life of your roof. It is designed for use over Mobil Homes, Asphalt Shingles, Metal Roofs, most Built-up roofs and as first coat over URETHANE FOAM.

501 - ACRYLIC IS A “BREATHER” and therefore allows moisture from the substrate to escape if allowed to totally dry before being covered with a VAPOR SEAL PRODUCT.

PREPARATION: Sweep and/or wash off all dirt, dust and debris. Seal around all roof intrusions (Vents, Pipes, Coolers, etc.) with NEOPRENE CEMENT or ACRYLIC CEMENT plus MEMBRANE.

APPLICATION: Apply only when coating will not be subjected to rain before it has dried. Do not apply on overcast days during winter months. 501- ACRYLIC needs six hours sunshine before rain. Coating can be applied to damp surfaces over 50 degrees with sunshine in winter and spreads best in extreme heat of summer when roof is fogged with water just prior to application or in the early morning. Coating must not be subjected to freezing before it has cured! Do not apply beyond 2 P.M. when temperature is under 75 degrees.

CLEAN UP: Hands and tools can be cleaned immediately with soap and water. After coating is dry, clean up can be best accomplished with ISOPROPYL ALCOHOL.

COVERAGE: Spread evenly at a rate of 1 gallon per 100 square feet.
(2 coats recommended)

APPLY: BRUSH, ROLL OR SPRAY. (35 mil tip is best!!)

SPECIFICATIONS:

RE-COAT: 4 hours summer - next day winter.
SERVICE TEMPERATURE: 0 degrees F - 200 degrees F
ELONGATION: 300% @ 100 degrees
MIL THICKNESS: 2 gals. per 100 square feet equals 15 mils.
SOLIDS: 62% (by weight)
FLASH POINT: NONE
WEIGHT: 11 ½ lbs. per gallon
FILM HARDNESS: soft and flexible
CAUTION: DO NOT THIN THIS MATERIAL!!



(480) 967-9407

3003 N. 73RD ST. SUITE 1 • SCOTTSDALE, ARIZONA 85251

HIGH PERFORMANCE ROOF COATINGS • PRIMERS • MEMBRANES
PATCHING COMPOUNDS • CAULKS • SEALANTS • DECK COATINGS