


PREMIUM GRADE ACRYLIC ELASTOMERIC



PREMIUM GRADE ACRYLIC ROOF COATING is ready to use and will seal and protect a variety of flat, sloped and horizontal surfaces.

This white reflective coating provides considerable cooling, and therefore lengthens the life of your roof. It has been specifically designed for use where pooling water accumulates and is highly recommended over URETHANE FOAM, most Built-Up Roofs and Asphalt Shingles.

PREPARATION:

Sweep off all dirt, dust and debris. Seal around roof vents, pipes and repair cracks, breaks and open seams with White Acrylic Cement or NEOPRENE Cement. Permit NEOPRENE Cement to dry overnight and White Acrylic Cement to dry 48 to 72 hours (when possible) before coating.

APPLICATION:

Apply only when coating will not be subject to rain before coating has dried.

PREMIUM GRADE ACRYLIC coating needs 6 hours sunshine in winter and 4 hours sunshine in summer to dry before rain ! Coating cannot be applied to wet or damp surfaces. During the winter season, coating must not be applied until morning dew has completely dissipated. When daily "high" temperature is 75 degrees or less, application must cease by 2:00 P.M. Coating should not be applied when roof temperature is less than 50 degrees F.

Hands and tools may be cleaned immediately after use with water. After coating is dry, clean up must be done with SOLVENT. ISOPROPYL ACOHOL IS BEST.

COVERAGE:

Spread or spray evenly at a rate of 1 gallon per 100 square feet.
Two coats recommended!

APPLY: Heavy Nap Roller or Airless Spray with 35 mil tip.

SPECIFICATIONS:

| | |
|-------------------------|--|
| RE-COAT: | Next day winter----4 hours summer |
| SURFACE TEMPERATURE: | between 50 and 200 degrees F |
| ELONGATION: | 240% @ 100 degrees F. |
| MIL THICKNESS: | 2 gallons per 100 square feet equals 15 dry mils |
| TOTAL SOLIDS BY WEIGHT: | 70% |
| FLASH POINT: | NONE |
| FIRE RATING: | CLASS A |
| WEIGHT: | 12 ½ lbs per gallon |
| FILM HARDNESS: | Soft and flexible |
| SHELF LIFE: | 2 years in unopened containers stored at room temperature. |

CAUTION DO NOT THIN THIS MATERIAL!!



(480) 967-9407

3003 N. 73RD ST. SUITE 1 • SCOTTSDALE, ARIZONA 85251

HIGH PERFORMANCE ROOF COATINGS • PRIMERS • MEMBRANES
PATCHING COMPOUNDS • CAULKS • SEALANTS • DECK COATINGS